

**DUAL-PLATE WAFER TYPE CHECK VALVE - C1 / C2 FOR ANIS / JIS / DIN INSTALLATION DIMENSIONS**  
**ANSI / JIS / DIN 雙門對夾式 - C1 / C2 止回閥安裝尺寸表**

Size	Class	Dimensions			Weight (kgs)
		AØ	B	EØ	
40(1-1/2")	*10K	86	54	60	3
	*125	86	54	60	3
	10K	86	60	60	3
	20K	86	60	60	3
	150	86	60	60	3
	300	95	60	60	3
50(2")	PN16	109	60	60	3
	PN25	109	60	60	3
	PN40	109	60	60	3.5
	*10K	101	54	60	3
	*125	105	54	60	3
	10K	101	60	60	3
	20K	101	60	60	3
	150	105	60	60	3
	300	111	60	60	3
	600	111	60	60	3
	900	143	70	60	6
	1500	143	70	60	7
2500	146	70	60	14	
65(2-1/2")	PN16	129	67	73	4
	PN25	129	67	73	4
	PN40	129	67	73	4
	*10K	121	54	73	4
	*125	124	54	73	4
	10K	121	67	73	4
	20K	121	67	73	5
	150	124	67	73	4
	300	130	67	73	4
	600	130	67	73	4
	900	165	83	73	7
	1500	165	83	73	8
2500	168	83	73	15	
80(3")	PN16	144	73	89	5
	PN25	144	73	89	5
	PN40	144	73	89	5
	*10K	131	57	89	5
	*125	137	57	89	5
	10K	131	73	89	6
	20K	137	73	89	7
	150	137	73	89	6
	300	149	73	89	7
	600	149	73	89	7
	900	168	83	89	13
	1500	175	83	89	14
2500	197	86	89	21	
100(4")	PN16	164	73	114	7
	PN25	170	73	114	7
	PN40	170	73	114	8
	*10K	156	64	114	6
	*125	175	64	114	6
	10K	156	73	114	8
	20K	162	73	114	8
	150	175	73	114	8
	300	181	73	114	8
	600	194	79	114	12
	900	206	102	114	18
	1500	210	102	114	21
2500	235	105	114	42	

Size	Class	Dimensions			Weight (kgs)
		AØ	B	EØ	
125(5")	PN16	194	86	141	11
	PN25	196	86	141	14
	PN40	196	86	141	20
	*10K	187	70	141	9
	*125	197	70	141	9
	10K	187	83	141	10
	20K	200	86	141	14
	150	197	86	141	10
	300	216	86	141	14
	600	241	105	141	23
150(6")	PN16	220	98	168	15
	PN25	226	98	168	19
	PN40	226	98	168	26
	*10K	217	76	168	10
	*125	222	76	168	10
	10K	217	98	168	16
	20K	235	98	168	19
	150	222	98	168	16
	300	251	98	168	19
	600	267	136	168	33
	900	289	159	168	53
	1500	283	159	168	59
2500	318	159	168	86	
200(8")	PN16	275	127	219	30
	PN25	286	127	219	35
	PN40	293	127	219	47
	*10K	267	95	219	19
	*125	279	95	219	19
	10K	267	127	219	32
	20K	280	127	219	36
	150	279	127	219	32
	300	308	127	219	36
	600	321	165	219	68
	900	359	206	219	97
	1500	352	206	219	97
2500	387	206	219	129	
250(10")	PN16	331	146	273	42
	PN25	343	146	273	45
	PN40	355	146	273	66
	*10K	330	108	273	31
	*125	340	108	273	31
	10K	330	146	273	47
	20K	353	146	273	51
	150	340	146	273	47
	300	362	146	273	51
	600	400	213	273	104
	900	435	241	273	132
	1500	435	248	273	140
2500	476	254	273	170	
300(12")	PN16	386	181	324	61
	PN25	403	181	324	63
	PN40	420	181	324	92
	*10K	375	143	324	56
	*125	410	143	324	56
	10K	375	181	324	84
	20K	403	181	324	88
	150	410	181	324	84
	300	422	181	324	88
	600	457	229	324	144
	900	498	292	324	169
	1500	521	305	324	178
2500	549	305	324	214	

備註: 除上述公稱尺寸/壓力外, 其它公稱尺寸/壓力亦有製作。

NOTE: Other dimensiona and class are available upon request.

Please contact with our sales department.

**DUAL-PLATE WAFER TYPE CHECK VALVE - C1 / C2 FOR ANIS / JIS / DIN INSTALLATION DIMENSIONS**  
**ANSI / JIS / DIN雙門對夾式 - C1 / C2 止回閥安裝尺寸表**

Size	Class	Dimensions			Weight (kgs)
		AØ	B	EØ	
350(14")	PN16	446	184	356	91
	PN25	460	184	356	102
	PN40	477	222	356	134
	*10K	420	184	356	71
	*125	451	184	356	71
	10K	420	184	356	97
	20K	447	222	356	176
	150	451	184	356	97
	300	486	222	356	176
	600	492	273	356	198
	900	521	356	356	198
1500	578	356	356	198	
400(16")	PN16	498	191	406	115
	PN25	517	191	406	122
	PN40	549	232	406	210
	*10K	483	191	406	99
	*125	514	191	406	99
	10K	483	191	406	159
	20K	507	232	406	227
	150	514	191	406	159
	300	540	232	406	227
	600	565	305	406	288
	900	575	384	406	550
1500	641	384	406	750	
450(18")	PN16	558	203	457	170
	PN25	567	203	457	478
	PN40	574	264	457	246
	*10K	538	203	457	118
	*125	549	203	457	118
	10K	538	203	457	185
	20K	572	264	457	301
	150	549	203	457	185
	300	597	264	457	301
	600	613	362	457	401
	900	638	451	457	770
1500	705	468	457	980	
500(20")	PN16	620	219	508	208
	PN25	627	219	508	226
	PN40	631	219	508	352
	*10K	593	213	508	180
	*125	606	213	508	180
	10K	593	219	508	243
	20K	627	292	508	373
	150	606	219	508	243
	300	654	292	508	373
	600	683	368	508	640
	900	699	451	508	1055
550(22")	*10K	647	219	559	210
	10K	647	219	559	231
600(24")	PN16	737	222	610	208
	PN25	734	222	610	226
	PN40	750	318	610	352
	*10K	697	222	610	258
	*125	718	222	610	258
	10K	697	222	610	394
	20K	731	318	610	598
	150	718	222	610	398
	300	775	318	610	598
	600	791	438	610	918
	900	838	495	610	1700

Size	Class	Dimensions			Weight (kgs)
		AØ	B	EØ	
550(22")	*10K	647	219	559	210
	10K	647	219	559	231
600(24")	PN16	737	222	610	208
	PN25	734	222	610	226
	PN40	750	318	610	352
	*10K	697	222	610	258
	*125	718	222	610	258
	10K	697	222	610	394
	20K	731	318	610	598
	150	718	222	610	398
	300	775	318	610	598
	600	791	438	610	918
	900	838	495	610	1700
650(26")	*10K	747	279	660	549
	10K	747	356	660	700
	150	775	356	660	700
700(28")	PN16	807	321	711	170
	PN25	836	321	711	178
	*10K	807	321	711	580
	10K	807	321	711	638
750(30")	*10K	867	305	762	450
	*125	882	305	762	450
	10K	867	330	762	580
800(32")	150	883	330	762	580
	300	953	398	762	923
	PN16	914	356	813	560
	PN25	945	356	813	643
900(36")	*10K	917	356	813	526
	10K	917	356	813	583
	150	940	356	813	635
	PN16	1014	368	914	670
	PN25	1045	368	914	706
	PN40	1088	484	914	1195
1000(40")	*10K	1017	368	914	656
	*125	1048	368	914	656
	10K	1017	387	914	685
	150	1048	387	914	685
	300	1118	489	914	1609
	PN16	1127	419	1016	1085
1050(42")	PN25	1131	419	1016	1134
	PN40	1158	419	1016	1260
	*10K	1121	419	1016	1010
	10K	1121	419	1016	1110
	150	1162	419	1016	1190
	*125	1219	432	1067	1260
1200(48")	150	1219	432	1067	1386
	10K	1341	524	1219	1926
	PN16	1345	524	1219	1895
	PN25	1386	524	1219	2298
	PN40	1404	629	1219	2756
	*125	1384	524	1219	2055
	10K	1341	524	1219	2119
	150	1384	524	1219	2180
300	1324	629	1219	2755	

備註: 除上述公稱尺寸/壓力外, 其它公稱尺寸/壓力亦有製作。  
 NOTE: Other dimensions and class are available upon request.  
 Please contact with our sales department.